

MARINI[®]

QUARRIES GROUP

SPHERICAL



PERFORATRICE
DRILLING UNIT
FOREUSE
BOHRMASCHINE

Quarry Line

IT

Tagliablocchi Spherical, leggero e maneggevole , di facile posizionamento in ogni condizione di lavoro , sia verticale che orizzontale. E' ideale per l'apertura di nuove cave, nell'esecuzione di perforazioni primarie al monte o per la riquadratura di blocchi di granito o marmo. Consente di incrementare la produzione migliorando le condizioni di lavoro dell'operatore.

La colonna porta perforatore può essere posizionata, a seconda delle necessità, al centro o a lato del binario di traslazione ed è fissata su un supporto sferico, brevettato, che permette l'esecuzione di fori perfettamente allineati ed inclinati

ENG

Spherical is a light and handy block-cutting machine, easily-positioned in all working conditions, both vertical and horizontal ones. It is ideal for opening new quarries and performing primary drilling at the mountain or squaring granite and marble blocks. This increases the production improving the operator's working conditions. The rock-drill holding column may be positioned in the middle or at the side of the translation rail, as needed; it is fixed onto a trademark spherical support that drills perfectly aligned holes, inclined in any direction. Equipped with a 2,00 m first starting drill steel .



CARATTERISTICHE E DATI TECNICI

- Struttura leggera e versatile per eseguire perforazioni in qualsiasi direzione e a filo piano cava
- Colonna per fioretto di partenza 2.00 mt
- Martello pneumatico MARINI MA 90 (22x108 mm / 25x108 mm)
- Motore pneumatico di avanzamento a palette con forza di trazione 480 Kg (daN)
- Puntone di fissaggio slitta con supporto sferico per l'esecuzione di fori in qualsiasi direzione
- Binario base e di prolunga lg. 3.00 / 4.00 mt con viti di livellamento e cunei di fissaggio
- Gruppo comandi pneumatico con lubrificatore di linea e pannello comandi orientabile

DIMENSIONI E PESI:

- Lunghezza colonna (fioretto 2000): 3000 mm
- Peso spherical completo con binario da 3.00 mt: 230Kg
- Consumo aria: 6000 lpm @ 7 bar

PERFORAZIONE ORIZZONTALE / HORIZONTAL DRILLING



TECHNICAL FEATURES

- Light structure suitable to drill in any direction and minimizing the step when drilling horizontally
- Slide stroke suitable for drill steel L 2.00 mt
- Pneumatic rock drill MARINI MA 90 (22x108 mm / 25x108 mm)
- Feeding pneumatic blade motor with tractive force of 480 kg (daN)
- Down jack with spheric support for drilling in any direction
- Base / extension track lg. 3.00 / 4.00 mt with leveling screws and fixing wedges
- Pneumatic control panel with centralized lubrication and positionable in any direction

DIMENSIONS AND WEIGHT:

- Column length (drill steel 2000): 3000 mm
- Weight spherical complete with 3.00 mt track: 230Kg
- Air cons. : 6000 lpm @7 bar (211 cfm @ 100 psi)

PERFORAZIONE VERTICALE / VERTICAL DRILLING





... working to grow together...

MARINI QUARRIES GROUP S.R.L.

Via Beura 44-28844 Villadossola (VB)-ITALY

Tel.+39 0324 575106 Fax. +39 0324 54096

Web site www.mariniqg.it

email: mariniqg@mariniqg.it

