

Characteristics	PHP 25	PHP 40	PHP 50	PHP 60	PHP 100	PHP 120	PHP 150
Hydraulic Cylinder	1	1	1	1	1	1	1
Capacity (t)	25	40	50	60	100	120	150
Power (kW/hp)	5,5/7,5	7,5/10	7,5/10	7,5/10	9/12,5	9/12,5	9/12,5
Work Flow (l/min)	77/6	65/9	51/8	51/8	61/16	61/16	73/16
Work Pressure (bar)	260	260	250	250	260	260	250
Tank (l)	150	150	150	150	200	200	200
Dimensions (LxWxH) (mm)	1,2x1,0x2,0	1,4x1,0x2,2	1,8x1,2x2,4	1,8x1,2x2,4	2,1x1,6x3,2	2,1x1,6x3,2	2,1x1,6x3,2
Table Dimensions (mm)	1000x400	1000x475	1200x600	1200x600	1500x830	1500x830	1500x830
Blades min. Opening (mm)	25	25	25	25	25	25	25
Blades Stroke (mm)	250	300	355	355	500-650	500-650	500-650
Number of Blades	4+4	4+4	6+6	6+6	8+8	8+8	10+10
Length Blades (mm)	200	200	300	300	400	400	500
Weight (kg)	1030	1220	1530	N.D	N.D	3600	4000
Down Time (s)	1,7	1,4	1,6	N.D	N.D	5,4	6,59
Up Time (s)	1	2,1	2,5	N.D	N.D	6,75	7,72
Cycle Time(s)	2,7	3,5	4,1	N.D	N.D	12,15	14,31
End of Stroke	Yes	Yes	Yes	N.D	N.D	Yes	Yes



ADVANTAGES

- Ease of stopping the cutting tool.
- Execution of various works (pavement, facades, rustic walls).
- High productivity and safety.
- Low maintenance.
- Better utilization of the stone.
- Table in 400 Brinell.
- Compact machine.
- Count time.
- Optional: cutting head with oscilating blades.