

Characteristics - TYPE A	PPT 120/150	PPT 200/240	PPT 240/300	PPT 300/400	PPT 400/600
Blades Length (mm)	600	1000	1500	2000	3000
Capacity (t)	120/150	200/240	240/300	300/400	400/600
Power (kW/hp)	9/12,5	11/15	15/20	18/25	18/25
Tools Stroke (mm)	440/540	440/540	440/540	440/540	440/540
Cylinders	1	2	2	2/3	3/4

Characteristics - TYPE B	PPTX 200/240	PPTX 240/300	PPTX 300/400	PPTX 400/600
Blades Length (mm)	1000	1500	2000	3000
Capacity (t)	200/240	240/300	300/400	400
Power (kW/hp)	11/15	15/20	18/25	18/25
Tools Stroke (mm)	440/540	440/540	440/540	440/540
Cylinders	2	2	2/4	4/6

TYPE A



TYPE B



ADVANTAGES

TYPE A

- Simple movement;
- Inferior tool is fixed.

Extras

- Cutting head with independent blades.

TYPE B

- Double Movement;
- Inferior and superior tool move at the same time;
- High precision on cutting.

Extras:

- Cutting head with independent blades;
- Lateral cut in the width between 1000 and 1500 mm.